



US 20030227441A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2003/0227441 A1**  
**Hioki et al.** (43) **Pub. Date: Dec. 11, 2003**(54) **DISPLAY INPUT DEVICE AND DISPLAY  
INPUT SYSTEM**(30) **Foreign Application Priority Data**Mar. 29, 2002 (JP) ..... 2002-093812  
May 17, 2002 (JP) ..... 2002-143181(75) Inventors: **Tsuyoshi Hioki**, Kanagawa-ken (JP);  
**Masahiko Akiyama**, Tokyo (JP);  
**Kenichi Kameyama**, Kanagawa-ken  
(JP); **Kazuki Taira**, Tokyo (JP); **Isao**  
**Mihara**, Tokyo (JP)**Publication Classification**(51) **Int. Cl.<sup>7</sup>** ..... **G09G 5/00**  
(52) **U.S. Cl.** ..... **345/156**

Correspondence Address:

**OBLON, SPIVAK, MCCLELLAND, MAIER &  
NEUSTADT, P.C.**  
**1940 DUKE STREET**  
**ALEXANDRIA, VA 22314 (US)**(73) Assignee: **Kabushiki Kaisha Toshiba**, Tokyo (JP)(21) Appl. No.: **10/401,584**(22) Filed: **Mar. 31, 2003**(57) **ABSTRACT**

A display input device comprises a display unit having a flexibility; and a first form change detection unit having a flexibility. The first form change detection unit is able to detect a deformation ascribed to the flexibility as a change in a electrical property. A display input system further comprises a display driving unit that supplies a display signal to the display unit and a signal judging unit that judges a input data based on the change in a electrical property in the first form change detection unit. The input of a first data can be performed by adding the deformation to the display input device.

